

The TBS4 is a high voltage, high current disc pack SCR employing a high di/dt gate structure. This gate design allows the SCR to be reliably operated at high di/dt and dv/dt conditions in various phase control applications. The shorter ceramic package offers reduced thermal resistance offering highest current rating available.

FEATURES:

- Low On-State Voltage
- High di/dt Capability
- High dv/dt Capability
- Hermetic Ceramic Package
- Excellent Surge and I²t Ratings

APPLICATIONS:

- DC Power Supplies
- Motor Controls
- AC Soft-Starters

ORDERING INFORMATION

Select the complete 12 digit Part Number using the table below.
EXAMPLE: TBS436250HDH is a 3600V - 2500A SCR with 250ma IGT and 12 inch gate and cathode potential leads.

PART	Voltage Rating $V_{DRM}-V_{RRM}$	Voltage Code	Current Rating I_{TAVG}	Current Code	Turn-Off t_q	Gate I_{GT}	Leads
TBS4	3600	36	2500	25	0	H	
	3400	34					
	3200	32			600us	250ma	12"
	3000	30			(typ.)	(max)	

Absolute Maximum Ratings

Characteristic	Symbol	Rating	Units
Repetitive Peak Voltage	$V_{DRM}-V_{RRM}$	3600	Volts
Average On-State Current, $T_C=70^{\circ}C$	$I_{T(Avg.)}$	2500	A
RMS On-State Current, $T_C=70^{\circ}C$	$I_{T(RMS)}$	3927	A
Average On-State Current, $T_C=55^{\circ}C$	$I_{T(Avg.)}$	2675	A
RMS On-State Current, $T_C=55^{\circ}C$	$I_{T(RMS)}$	4202	A
Peak One Cycle Surge Current, 60Hz, $V_R=0V$	I_{TSM}	34,000	A
Peak One Cycle Surge Current, 50Hz, $V_R=0V$	I_{TSM}	32,055	A
Fuse Coordination I^2t , 60Hz	I^2t	4.82E+06	A ² s
Fuse Coordination I^2t , 50Hz	I^2t	5.14E+06	A ² s
Critical Rate-of-Rise of On-State Current Repetitive .67•VDRM	di/dt	100	A/us
Critical Rate-of-Rise of On-State Current Non-Repetitive .67•VDRM	di/dt	200	A/us
Peak Gate Power, 100us	P_{GM}	16	Watts
Average Gate Power	$P_{G(avg)}$	5	Watts
Operating Temperature	T_j	-40 to+125	°C
Storage Temperature	$T_{Stg.}$	-50 to+150	°C
Approximate Weight		2.5	lb
		1.13	Kg
Mounting Force		9000-10000	lbs
		40 - 44.5	KNewtons

Information presented is based upon manufacturers testing and projected capabilities. This information is subject to change without notice. The manufacturer makes no claim as to suitability for use, reliability, capability or future availability of this product.

Electrical Characteristics, T_j=25°C unless otherwise specified

Characteristic	Symbol	Test Conditions	Rating			Units
			min	typ	max	
Repetitive Peak Forward Leakage Current	I _{DRM}	T _j =125°C, V _{DRM} =Rated			200	ma
Repetitive Peak Reverse Leakage Current	I _{RRM}	T _j =125°C, V _{RRM} =Rated			200	ma
Peak On-State Voltage	V _{TM}	T _j =125°C, I _{TM} =2000A			1.50	V
V _{TM} Model, Low Level	V ₀	T _j =125°C			1.026	V
V _{TM} = V ₀ + r•I _{TM}	r	15% I _{TM} - π•I _{TM}			0.233	mΩ
V _{TM} Model, High Level	V ₀	T _j =125°C			1.175	V
V _{TM} = V ₀ + r•I _{TM}	r	π•I _{TM} - I _{TSM}			0.208	mΩ
V _{TM} Model, 4-Term	A	T _j =125°C			0.120	
V _{TM} = A + B•Ln(I _{TM}) +	B	15% I _{TM} - I _{TSM}			0.146	
C•(I _{TM}) + D•(I _{TM}) ^{1/2}	C				0.000212	
	D				-0.00344	
Turn-On Delay Time	t _d	V _D = 0.5•V _{DRM} Gate Drive: 40V - 20Ω			3.5	us
Turn-Off Time	t _q	T _j =125°C dv/dt = 20V/us to 80% V _{DRM}			600	us
Reverse Recovery Current	I _{R(Rec)}	T _j =125°C 1500A -10A/us				A
Reverse Recovery Charge	Q _{RR}					uCoul
dv/dt _(Crit)	dv/dt	T _j =125°C Exp. Waveform V _D =80% Rated	1000			V/us
Gate Trigger Current	I _{GT}	T _j =25°C V _D = 12V	30	150	250	ma
Gate Trigger Voltage	V _{GT}		0.8	2.0	4.0	V
Peak Reverse Gate Voltage	V _{GRM}				5	V

Thermal Characteristics

Characteristic	Symbol	Test Conditions	Rating			Units
			min	typ	max	
Thermal Resistance						
Junction to Case	Rθ _{jc}	Double side cooled		0.0075	0.0085	°C/Watt
Case to Sink	Rθ _{cs}	Double side cooled		0.0015	0.002	°C/Watt

Thermal Impedance Model Zθ_{jc} Double side cooled


$$Z\theta_{jc}(t) = \sum(A(N) \cdot (1 - \exp(-t/\text{Tau}(N))))$$

where: N = 1 2 3 4


A(N) = 1.13E-04 7.51E-04 3.53E-03 4.11E-03

Tau(N) = 6.54E-04 1.48E-02 1.89E-01 6.00E-01


Maximum On-State Voltage Drop




MAXIMUM TRANSIENT THERMAL IMPEDANCE




Maximum On-State Power Dissipation



Maximum Allowable Case Temperature
Sinusoidal Waveform



Maximum On-State Power Dissipation



Maximum Allowable Case Temperature
Square Waveform

